

Printing date 05/12/2021 Reviewed on 04/09/2021

1 Identification

· Product identifier: PZ-16-A

· Trade name: CANTESCO® PREMIUM ZINC RICH SPRAY GALV (MATTE FINISH)

· Item number(s): PZ-16-A

· SDS Number: 280

· UPC bar code(s): 699913-125605

· Application of the substance / the mixture SPRAY GALV

· Manufacturer/Supplier: WWW.CANTESCO.COM

USA ADDRESS:

KEMPER SYSTEM AMERICA, INC. 1200 NORTH AMERICA DR, WEST SENECA, NY 14224 PH (716) 558-2971

111 (710) 336-2371

CANADIAN ADDRESS: ASTARAS CANADA, INC. 4-7075 EDWARDS BLVD MISSISSAUGA, ONTARIO, L5S 1Z2

PH (905) 624-5463

· Information department:

Tel: (716) 558-2971 ext. 228

www.cantesco.com

· Emergency telephone number:

ChemTrec (800) 424-9300 / 1-(703)-741-5970

Canada only: CANUTEC (Call collect) (613) 996-6666

2 Hazard identification

· Classification of the substance or mixture:



Flammable Aerosols - Category 1

H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.



GHS04 Gas cylinder

Gases Under Pressure - Compressed Gas H280 Contains gas under pressure; may explode

if heated.



GHS08 Health hazard

Carcinogenicity – Category 2 H351 Suspected of causing cancer.

Reproductive Toxicity - Category 2 H361 Suspected of damaging fertility or the

unborn child.

Specific Target Organ Toxicity - Repeated Exposure - H373 May cause damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 2)

Printing date 05/12/2021 Reviewed on 04/09/2021

Trade name: CANTESCO® PREMIUM ZINC RICH SPRAY GALV (MATTE FINISH)

(Contd. of page 1)



Eye Irritation - Category 2A H319 Causes serious eye irritation.

Skin Sensitizer - Category 1 H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure - H336 May cause drowsiness or dizziness.

Category 3

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Signal word: Danger

· Hazard-determining components of labeling:

butanone

n-hexane

ethylbenzene

· Hazard statements:

H222-H229 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P233 Keep container tightly closed.

P251 Do not pierce or burn, even after use. P260 Do not breathe mist/vapors/spray. P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P403 Store in a well-ventilated place.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 3)

Printing date 05/12/2021 Reviewed on 04/09/2021

Trade name: CANTESCO® PREMIUM ZINC RICH SPRAY GALV (MATTE FINISH)

(Contd. of page 2)

- · Information pertaining to particular dangers for man and environment:
- · NFPA ratings (scale 0 4):



3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous	· Dangerous components:		
78-93-3	butanone	30-60% w/w *	
74-98-6	propane	10-30% w/w *	
106-97-8	butane	≤10% w/w	
75-28-5	isobutane	≤10% w/w	
64742-47-8	Distillates (petroleum), hydrotreated light	1-5% w/w *	
110-54-3	n-hexane	≤5% w/w	
1330-20-7	xylene	1-5% w/w *	
100-41-4	ethylbenzene	0.1-≤1% w/w *	

^{*} Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

- · General information: Symptoms of poisoning may even occur after several hours.
- After inhalation:

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

After skin contact:

Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or a rash occurs: Get medical advice/attention.

· After eve contact:

Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists get medical advice/attention.

- · After swallowing: Do not induce vomiting, Immediately call a poison center/ doctor.
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-fighting measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture: No further relevant information available.

(Contd. on page 4)

Printing date 05/12/2021 Reviewed on 04/09/2021

Trade name: CANTESCO® PREMIUM ZINC RICH SPRAY GALV (MATTE FINISH)

· Protective equipment: No special measures required.

(Contd. of page 3)

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling
- · Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

- ·Storage
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s): No further relevant information available.

8 Exposure controls/ Personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)

Printing date 05/12/2021 Reviewed on 04/09/2021

Trade name: CANTESCO® PREMIUM ZINC RICH SPRAY GALV (MATTE FINISH)

	(Contd. o	of page
	with limit values that require monitoring at the workplace:	
78-93-3 buta		
EL (Canada)	Short-term value: 100 ppm	
	Long-term value: 50 ppm	
EV (Canada)	Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm	
PEL (USA)	Long-term value: 590 mg/m³, 200 ppm	
REL (USA)	Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm	
TLV (USA)	Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm BEI	
74-98-6 prop	ane	
EL (Canada)	Long-term value: 1000 ppm	
EV (Canada)	Long-term value: 1,000 ppm	
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm	
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm	
TLV (USA)	refer to Appendix F inTLVs&BEIs book; NIC-EX	
106-97-8 but	ane	
EL (Canada)	Short-term value: 750 ppm Long-term value: 600 ppm	
EV (Canada)	Long-term value: 800 ppm	
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm	
TLV (USA)	Short-term value: (2370) mg/m³, (1000) ppm NIC-EX	
75-28-5 isobu	ıtane	
EV (Canada)	Long-term value: 800 ppm	
TLV (USA)	Short-term value: (2370) mg/m³, (1000) ppm NIC-EX	
64742-47-8 D	Distillates (petroleum), hydrotreated light	
EL (Canada)	Long-term value: 200 mg/m³ Skin	
110-54-3 n-h	exane	
EL (Canada)	Long-term value: 20 ppm Skin	
EV (Canada)	Long-term value: 176 mg/m³, 50 ppm	
PEL (USA)	Long-term value: 1800 mg/m³, 500 ppm	
REL (USA)	Long-term value: 180 mg/m³, 50 ppm	
TLV (USA)	Long-term value: 176 mg/m³, 50 ppm Skin; BEI	
1330-20-7 xy	lene	
EL (Canada)	Short-term value: 150 ppm Long-term value: 100 ppm	
EV (Canada)	Short-term value: 650 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
	(Contd. o	n pag

Printing date 05/12/2021 Reviewed on 04/09/2021

Trade name: CANTESCO® PREMIUM ZINC RICH SPRAY GALV (MATTE FINISH)

		(Contd. of page 5)
	PEL (USA)	Long-term value: 435 mg/m³, 100 ppm
	REL (USA)	Short-term value: 655 mg/m³, 150 ppm
		Long-term value: 435 mg/m³, 100 ppm
	TLV (USA)	Short-term value: 651 mg/m³, 150 ppm
		Long-term value: 434 mg/m³, 100 ppm
\vdash	100-41-4 eth	BEI
-		Long-term value: 20 ppm
	, , ,	IARC 2B
	EV (Canada)	Short-term value: 540 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm
	DEL (LICA)	
	PEL (USA)	Long-term value: 435 mg/m³, 100 ppm
	REL (USA)	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm
	TLV (USA)	Long-term value: 87 mg/m³, 20 ppm BEI
	·Ingredients	with biological limit values:
	78-93-3 buta	none
	BEI (USA)	
		Medium: urine
		Time: end of shift Parameter: MEK
\vdash	110-54-3 n-h	
\vdash	BEI (USA)	
		Medium: urine
	5	Time: end of shift at end of workweek
	1	Parameter: 2.5-Hexanedione without hydrolysis
	1330-20-7 xy	
	BEI (USA)	1.5 g/g creatinine
		Medium: urine
		Time: end of shift Parameter: Methylhippuric acids
-	100-41-4 eth	, 11
\vdash		0.7 g/g creatinine
		Medium: urine
	-	Time: end of shift at end of workweek
		Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
	-	-
	1	Medium: end-exhaled air
		Time: not critical
L		Parameter: Ethyl benzene (semi-quantitative)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

(Contd. on page 7)

Printing date 05/12/2021 Reviewed on 04/09/2021

Trade name: CANTESCO® PREMIUM ZINC RICH SPRAY GALV (MATTE FINISH)

(Contd. of page 6)

- · Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves:

Butyl rubber, BR Nitrile rubber, NBR

· Eye protection:



Tightly sealed goggles

9 Physical and chemical proper	rties
· Form: · Color: · Odor: · Odor threshold:	Liquid Under Pressure Grey Solvent-like Not determined.
· pH-value:	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 69 °C
· Flash point:	-27 °C
Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	210 °C
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits Lower: Upper:	1.5 Vol % 11.5 Vol %
· Vapor pressure at 20 °C:	8300 hPa
 Density at 20 °C: Relative density: Vapor density at 20 °C: Evaporation rate: 	0.91 g/cm ³ Not determined. 2.970 g/cm ³ Not applicable.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water	er): Not determined.

(Contd. on page 8)

Printing date 05/12/2021 Reviewed on 04/09/2021

Trade name: CANTESCO® PREMIUM ZINC RICH SPRAY GALV (MATTE FINISH)

(Contd. of page 7) · Viscosity: **Dynamic:** Not determined. **Kinematic:** Not determined. · Solvent content: 120.9 % **VOC** content: 1100.2 g/l / 9.18 lb/gl · Other information No further relevant information available.

10 Stability and reactivity

- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: Reacts with oxidizing agents.
- Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects:
- · Acute toxicity

· LD/LC50 values that are relevant for classification:			
78-93-3	78-93-3 butanone		
Oral	LD50	3300 mg/kg (rat)	
Dermal	LD50	5000 mg/kg (rabbit)	

- · Specific symptoms in biological assay: No further relevant information available.
- · Primary irritant effect
- on the skin: Irritant to skin and mucous membranes.
- · on the eve: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
1330-20-7 xylene	3
100-41-4 ethylbenzene	2B
· NTP (National Toxicology Program)	

None of the ingredients is listed.

12 Ecological information

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability: No further relevant information available.
- Behavior in environmental systems
- · Bioaccumulative potential: No further relevant information available.

(Contd. on page 9)

Printing date 05/12/2021 Reviewed on 04/09/2021

Trade name: CANTESCO® PREMIUM ZINC RICH SPRAY GALV (MATTE FINISH)

(Contd. of page 8)

- · Mobility in soil: No further relevant information available.
- · Ecotoxical effects:
- · Remark: Very toxic for fish
- · Additional ecological information
- · General notes:

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· Other adverse effects: No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings
- Recommendation:

Place in a sealed container and label as waste. Place in a safe area, and comply with all federal, state, provincial and local regulations for disposal.

14 Transport information

UN	-N	ıım	ber	
	- 1	um	Dei	

· DOT/TDG, ADR, IMDG, IATA UN1950

· UN proper shipping name

DOT/TDG Aerosols, flammable
ADR 1950 Aerosols
IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · Transport hazard class(es)
- · DOT/TDG (Transport dangerous goods):



· Class 2.1 · Label 2.1

· ADR



· Class 2 5F Gases

(Contd. on page 10)

Printing date 05/12/2021 Reviewed on 04/09/2021

Trade name: CANTESCO® PREMIUM ZINC RICH SPRAY GALV (MATTE FINISH)

	(Contd. of page
Label	2.1
· IMDG, IATA	
· Class · Label	2.1 2.1
Packing group DOT/TDG, ADR, IMDG, IATA	Not regulated
Environmental hazards: Marine pollutant:	Yes
Special precautions for user:	Warning: Gases
Hazard identification number (Kemler code) EMS Number:): - F-D,S-U
· EMS Number: · Stowage Code	SW1 Protected from sources of heat.
Storinge Couc	SW22 For AEROSOLS with a maximum capacity of 1 litre
	Category A. For AEROSOLS with a capacity above 1 litre
	Category B. For WASTE AEROSOLS: Category C, Clear of
	living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre:
	Segregation as for class 9. Stow "separated from" class 1 excep
	for division 1.4. For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:	Not applicable.
	Not applicable.
Transport/Additional information:	
· DOT/TDG	On massangan ainanaft/mili 75 lta
Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
Remarks:	This product may be shipped according to the Limited Quantit
	Exceptions provided that all Limited Quantity shippin
	requirements are met.
· ADR	
Excepted quantities (EQ)	Code: E0
_	Not permitted as Excepted Quantity
Remarks:	This product may be shipped according to the Limited Quantit Exceptions provided that all Limited Quantity shippin requirements are met.
· IMDG	
Limited quantities (LQ)	1L
	1L Code: E0 Not permitted as Excepted Quantity

Printing date 05/12/2021 Reviewed on 04/09/2021

Trade name: CANTESCO® PREMIUM ZINC RICH SPRAY GALV (MATTE FINISH)

	(Contd. of page 10
· Remarks:	This product may be shipped according to the Limited Quantity Exceptions provided that all Limited Quantity shipping requirements are met.
· IATA · Remarks:	This product may be shipped according to the Limited Quantity Exceptions provided that all Limited Quantity shipping requirements are met.
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

Section 355 (extremely hazardous substances):	
---	--

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

	butanone
110-54-3	n-hexane
1330-20-7	xylene

100-41-4 ethylbenzene

· TSCA (Toxic Substances Control Act):

All ingredients are listed or exempted

· Proposition 65

· Chemicals known to cause cancer:

100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Canadian substance listings

· Canadian Domestic Substances List (DSL/NDSL):

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%):

100-41-4 ethylbenzene

· Canadian Ingredient Disclosure list (limit 1%):

	butanone
106-97-8	butane

110-54-3 n-hexane

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 12)

(Contd. of page 11)

Safety Data Sheet according to HPR, Schedule 1

Printing date 05/12/2021 Reviewed on 04/09/2021

Trade name: CANTESCO® PREMIUM ZINC RICH SPRAY GALV (MATTE FINISH)

· Hazard pictograms









GHS02

GHS04 GH

GHS07 GHS0

· Signal word Danger

$\cdot \ Hazard\text{-}determining \ components \ of \ labeling:$

butanone

n-hexane

ethylbenzene

Hazard statements

H222-H229 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

16 Other information

This SDS format meets ANSI Z400.1-2010, OSHA 1910.1200 and WHMIS requirements. Kemper System America, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Product use and conditions of use are beyond the control of Kemper System America, Inc. Warranty of materials is limited to test results of product performance as detailed in certificates of compliance. Interpretation of test results is the responsibility of end-user. No other warranties, expressed or implied, are made. Kemper System America, Inc is an ISO 9001:2015 and ISO 14001:2015 registered company.

- · Department issuing SDS: Product safety department
- Contact: Stephen Nowicki
- · Date of the latest revision of the safety data sheet 05/12/2021 / -
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

CA -